

A-80 2D Image Platform Scanner

Features

- ❖ Wide field-of-view, Omni-directional scanning capability.
- ❖ 300,000 pixels global shutter.
- ❖ Fast decoding speeds at 120 FPS/s.
- ❖ Minimum resolution: 4 mils
- ❖ Read all mainstream 1D&2D barcodes.
- ❖ The ideal option for rapid work.
- ❖ Easily read even high-precision, wrinkled, damaged, or poorly printed barcodes.



☆ Detailed display



Guangzhou AiGather Intelligent Technology co., LTD

📍 2F, Building B, Zhongming Industrial Park, No. 2 Fuling Road, Zengcheng District, Guangzhou, China www.aigather.com

A-80 2D Image Platform scanner

Technical Specification

Performance Parameter																									
Light Source	LED Red light (Germany)																								
Image sensor	640*480 pixels																								
Resolution(maximum)	0.102mm / 4mils																								
Print contrast ratio(minimum)	≥20%																								
Motion tolerance	2M/sec																								
Reading Angle	Pitch: 0-360°; Roll(Tilt): ±60°; Skew (Yaw): ±60°																								
Decoding Capability	1D: All standard 1D codes, including GS1 DataBar™ linear code can be automatically distinguished and decoded. 2D: Aztec Code; Data Matrix; MaxiCode; QRCode; HANXIN; MicroQR Code Stack code: GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; GS1 DataBar Composite; MicroPDF417; PDF417.																								
Reading Indicators	LED light & Buzzer(adjustable tone and volume)																								
Typical depth of Filed	<table border="1"> <thead> <tr> <th>Precision</th> <th>Barcode</th> <th>Depth of Filed</th> </tr> </thead> <tbody> <tr> <td>5mil</td> <td>CODE128</td> <td>1mm—80mm</td> </tr> <tr> <td>5mil</td> <td>EAN-13</td> <td>1mm—80mm</td> </tr> <tr> <td>13.34mil</td> <td>EAN-13</td> <td>5mm—245mm</td> </tr> <tr> <td>5mil</td> <td>PDF417</td> <td>5mm—70mm</td> </tr> <tr> <td>10mil</td> <td>PDF417</td> <td>5mm—180mm</td> </tr> <tr> <td>15mil</td> <td>PDF417</td> <td>10mm—280mm</td> </tr> <tr> <td>20mil</td> <td>DM</td> <td>5mm—80mm</td> </tr> </tbody> </table> <p>(The minimum depth of field is determined by the barcode length and scanning angle. It depends on the print resolution, contrast and ambient light.)</p>	Precision	Barcode	Depth of Filed	5mil	CODE128	1mm—80mm	5mil	EAN-13	1mm—80mm	13.34mil	EAN-13	5mm—245mm	5mil	PDF417	5mm—70mm	10mil	PDF417	5mm—180mm	15mil	PDF417	10mm—280mm	20mil	DM	5mm—80mm
Precision	Barcode	Depth of Filed																							
5mil	CODE128	1mm—80mm																							
5mil	EAN-13	1mm—80mm																							
13.34mil	EAN-13	5mm—245mm																							
5mil	PDF417	5mm—70mm																							
10mil	PDF417	5mm—180mm																							
15mil	PDF417	10mm—280mm																							
20mil	DM	5mm—80mm																							
Physical characteristics																									
Color available	Black & Orange & Blue																								
Dimensions (L*W*H)	112*101*164mm																								
Weight	313g																								
Cable	1.6m																								
Electrical Parameter																									
Current	Working current (Standard): < 300 mA Standby current (Standard): < 210 mA																								
Input Voltage	5 VDC (+/- 10%)/500mA																								
Environmental Parameter																									
ESD protection(Air discharge)	8 kV																								
Drop resistance	Withstands repeated drops from 1.2m/4.0 ft onto a concrete surface.																								
Particulate and water sealing	IP52																								
Temperature	Operation: 0 to 40 °C Storage/Transport: -40 to 70 °C																								
Humidity(non-condensing)	5 - 95%																								
Ambient light	0 -100,000 lux																								
Interfaces																									
Interfaces	RS-232; USB HID; USB COM; HID POS available as per customer's needs																								
Warranty																									
	18/months																								