



XL-2001

- With CE, FCC certificates
- Firmware can be upgraded online
- Laser & motor automatically dormant, quickly wake up
- 20 scan lines at a rate of 1,500 scans per second
- Plug and play, no need any driver, easy operation.
- Support USB, Keyboard, RS-232 interfaces



Omnidirectional Barcode Scanner

Light Source	Visible Laser Diode 650nm
Scan Pattern	20 lines 5 fields of 4 parallel lines
Scan speed	1500 scans/s
Print Contrast	30% @ UPC/EAN 100%
Minimum Resolution	5mil@PCS90%
Depth of Field	0-220mm for 0.33mm UPC/EAN100%
Host System Interfaces	USB, RS232, Keyboard Wedge
Visual Indicators	Two color LED (blue & red)
Beeper Operation	Programmable tone & volume
Cable	Standard 2M straight

Size	L × W × H: 100mm × 111mm × 147mm
Weight	310g
Material	ABS+PC
Laser Class	Meet the Grade I National Criteria for Laser Safety
Voltage	5 Volts
Static Current	250mA
EMC	CE & FCC DOC compliance
Operating Temperature	- 0°C to 45°C
Storage Temperature	- 20°C to 60°C
shock	Designed to 1.5m drops



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F, No.7, Kehui First Street, Science Road, Science City, Guangzhou, China
 Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com